

Benefits

- Save money by reducing installation costs
- Installation speed, flexibility, and simplicity
- Enable mobility that may not have been possible before
- No leased lines or wireless services cost
- Single radio module for worldwide license-free operation
- Low latency for real-time applications

Features

- 900 MHz frequency hopping spread spectrum technology
- RS-232 and RS-485 data interfaces supported
- Automatic antenna diversity options available
- Outdoor model available in weather tight NEMA 4X Housing
- Remote diagnostics
- User programmable

BINMASTER
Taking Control...To A Higher Level

Division of Garner Industries
7201 N. 98th Street
Lincoln, NE 68507
Fax (402) 434-9133
(402) 434-9102
www.binmaster.com

1-800-278-4241

HVS
PRECONISATEUR DE SOLUTIONS DEPUIS 1985

2 rue René Laennec 51500 Taissy France
Fax: 03 26 85 19 08, Tel : 03 26 82 49 29

E-mail: hvssystem@hvssystem.com
Site web : www.hvssystem.com


SmartBob II Wireless Network Solutions



PC Running IMS Software with Outdoor Wireless Transceiver

BinMaster's new wireless data transceiver eliminates the need for running long spans of communication cable by providing affordable, two-way wireless data communication between SmartBob II Remotes mounted high on-top of storage vessels and a control source on the ground. BinMaster's long-range wireless data transceiver operates in the license-free portion of the FCC designated industrial frequency band at 900 MHz.


Designed to work in high interference environments, the wireless transceivers combine advanced frequency hopping and digital signal processing technology with outstanding receiver sensitivity and antenna diversity resulting in exceptional noise and interference rejection and peace of mind for you. Wireless data networks can be effective in new SmartBob II installations as an alternative to wired connections and can also be used to expand the capabilities of existing systems.




Yagi Directional Antenna Option

SmartBob II Remote Sensor with Outdoor Wireless Transceiver


Point-to-Point single network wireless solution eliminates running RS-485 communication cable from the control source on the ground to the first SBR II remote in a single grouping of vessels.



Multi-Point single network wireless solution eliminates running RS-485 communication cable from the control source on the ground to the first SBR II remote in multiple groups of vessels.



Point-to-Point & Multi-Point multiple network wireless solution eliminates running RS-485 communication cable from the control source on the ground using two wireless data transceivers to the first SBR II remote in multiple groups of vessels.



BINMASTER
Taking Control... To A Higher Level

Division of Garner Industries
7201 N. 98th Street
Lincoln, NE 68507
Fax (402) 434-9133
(402) 434-9102
www.binmaster.com

1-800-278-4241

* Actual operating range depends on local environment, including obstructions and electrical interference



2 rue René Laennec 51500 Taissy France
Fax: 03 26 85 19 08, Tel : 03 26 82 49 29

E-mail: hvssystem@hvssystem.com
Site web : www.hvssystem.com